

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 January 2002 (17.01.2002)

PCT

(10) International Publication Number
WO 02/03863 A1

(51) International Patent Classification⁷: A61B 6/00, 5/055

(21) International Application Number: PCT/EP01/07254

(22) International Filing Date: 27 June 2001 (27.06.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
00202448.7 10 July 2000 (10.07.2000) EP

(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(74) Agent: SCHOUTEN, Marcus, M.; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated State (*national*): JP.

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).


Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- entirely in electronic form (except for this front page) and available upon request from the International Bureau

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventor: VAN VAALS, Johannes, J.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(54) Title: GEOMETRY MATCHING FOR IMAGING MEDICAL APPARATUS



(57) **Abstract:** Anatomical matching of images acquired by different imaging modalities plays an important role in diagnostic medical imaging. In common medical practice such matching takes place after the acquisition of the data sets containing the information to be matched and while utilizing standard post-processing algorithms. The invention provides a method for the acquisition of anatomically matched images while using the information concerning the position and orientation of the first imaging modality (1) relative to the object. Upon selection of a relevant image from the primary data set acquired by means of the first imaging modality, the co-ordinates which unambiguously define the position of the first imaging apparatus relative to this image are defined. These co-ordinates are made available to the second imaging modality (2) which is adjusted in conformity therewith. The image acquired by the second imaging modality will thus be anatomically matched with the primary image.



WO 02/03863 A1

Geometry matching for imaging medical apparatus

The invention relates to a method of generating anatomically matching images by means of a system which includes at least two imaging medical apparatus.

The invention also relates to a system for carrying out the method.

In contemporary medical practice it is often desirable to examine a patient by
5 means of a plurality of imaging medical apparatus, each imaging medical apparatus producing its own data set for diagnosis or further treatment. The evaluation of cranial disorders is an example of such multi-facility diagnosis. It is known that an MR apparatus constitutes a suitable diagnostic facility for the imaging of soft tissues. In the case of, for example, a cranial tumor it may be desirable to image a region of interest of the patient
10 further by means of, for example a CT apparatus and possibly additionally by means of a PET scanner. For the determination of the location of the disorder it is necessary to compare and match the volume data produced by such imaging medical apparatus. In contemporary medical practice all sets of volume data are acquired independently of one another; the matching of the geometries so as to realize anatomically matching images is performed in
15 retrospect by selection and computer reconstruction of the relevant data sets.

Such a method for retrospective matching of the geometries for different images produced by imaging medical apparatus is known from the article by F.W. Zonneveld
20 "A decade of clinical three-dimensional imaging: a review", Investigative Radiology, 29, No. 7, 1994. The cited publication discloses a method for the matching of anatomically corresponding images from data sets already produced by different imaging medical apparatus. The objects to be imaged may be a variety of cranial disorders, for example tumors or neurovascular anomalies. The known method for matching the objects to be
25 imaged utilizes a pattern recognition algorithm in combination with other algorithms, for example, an image reconstruction algorithm. The known matching method has a drawback in that the matching of the relevant objects can take place only in retrospect, so that the matching of the images could be affected by geometrical distortion of the original images. Moreover, such matching methods generally are very time-consuming and their success is

highly dependent on the matching algorithm used. Furthermore, execution of such methods necessitates interaction with the user. These problems become critical notably in the case of cranial interventions which must not only be fast but also very precise so as to minimize any side effects of the intervention.

5

It is an object of the present invention to provide a method of producing anatomically corresponding images by matching the geometries of different imaging medical apparatus in prospective. To this end, the method in accordance with the invention is

10 characterized in that it includes: acquisition of a data set containing a first image by means of a first apparatus; selection of a plane containing the first image from the data set; assignment of first co-ordinates relative to the first apparatus to the plane containing the first image; making the first co-ordinates available to the second apparatus; adjustment of the second apparatus in conformity with the first co-ordinates; formation of the second image while

15 utilizing said adjustment. In conformity with this method an initial acquisition of the data set of a patient is performed by means of the first imaging medical apparatus. In order to relate the spatial position and the orientation of this data set to the spatial adjustment of the first imaging medical apparatus, co-ordinates relative to the first imaging medical apparatus are assigned to said data set. Generally speaking, the data set may be a two-dimensional data set

20 or a three-dimensional data set. A two-dimensional data set is limited to a cross-section of the patient; a three-dimensional data set may contain a number of two-dimensional planes or may consist of intrinsic three-dimensional volume data, that is, no structure of planes is distinguished yet upon storage of this data. Generally speaking, a plane containing information that is relevant to the diagnosis does not correspond to one of the planes of the

25 original two-dimensional data set. A selection step for selecting or reconstructing a plane containing the first image is also required when the data set is a three-dimensional volume data set. This data processing step can be performed by means of reconstruction algorithms that are known per se. After selection of the plane containing the first image, the first co-ordinates relative to the first imaging medical apparatus are assigned to this plane. The first

30 plane is thus characterized relative to the first imaging medical apparatus. In order to produce an anatomically corresponding image with the second imaging medical apparatus, this apparatus must be adjusted in conformity with the first co-ordinates. This becomes possible by making the first co-ordinates available to the second apparatus. Generally speaking, it is desirable that for the adjustment of the second apparatus in conformity with the first co-

ordinates the second apparatus performs a so-called co-ordinate transformation operation so as to calculate own co-ordinates that define a second plane that corresponds to the first plane. A number of imaging medical apparatus could act as the first imaging medical apparatus in the system. In that case the execution of the co-ordinate transformation necessitates the storage of reference co-ordinates for every other imaging medical apparatus in the second imaging medical apparatus. After the second apparatus has been adjusted in conformity with the first co-ordinates, the second image is formed; this second image anatomically corresponds to the first image.

A first version of the method in accordance with the invention is characterized in that the first co-ordinates are made available by means of a computer included in the system. The computer in this version writes in the first co-ordinates of the first imaging medical apparatus. This version offers the advantage that the computer can be arranged in such a manner that the first co-ordinates are made available in a format that suits the second imaging medical apparatus. This may be necessary in a situation where the formats of the first and the second imaging medical apparatus are not compatible. A further advantage of the incorporation of a computer in the system consists in the fact that the computer can be arranged as a central computer in which all information concerning the patients is stored so as to avoid patient identification errors. The presence of a central computer simplifies the data transport between the imaging apparatus in case an essential pause is inserted between the first and subsequent acquisitions of the images. Moreover, the communication protocol of the system may be conceived such that the second imaging medical apparatus itself approaches the central computer concerning the availability of the first co-ordinates.

A further version of the method in accordance with the invention is characterized in that for each connected imaging medical apparatus a reference co-ordinate system is stored in a table present in the computer. This version offers the advantage that all information concerning the reference co-ordinates is stored in the computer so that the individual imaging medical apparatus will not have to follow up on up-to-date information concerning any changes in the configuration of other imaging medical apparatus, for example in a situation where new apparatus have been added or apparatus thus far present have been removed.

A further version of the method in accordance with the invention is characterized in that the second reference co-ordinate system is calculated from the first reference co-ordinate system by the computer. This version offers the advantage that the

second imaging medical apparatus does not have to perform the co-ordinate transformation operation, all co-ordinate transformations being performed in the computer.

A further version of the method in accordance with the invention is characterized in that the first co-ordinates are made available via a cable which directly
5 interconnects two imaging medical apparatus. This special version is intended for a situation where a number of imaging medical apparatus, for example two apparatus, co-operate in such a manner that a direct exchange of information is necessary. The use of a cable between these two medical apparatus offers the advantage that the cable for the data transmission is less susceptible to interference than a network or a radio link. An example of such a system with
10 two imaging medical apparatus consists of a combination of an MR apparatus and an X-ray apparatus, both of said apparatus being used, for example to carry out a cardiovascular intervention. During this intervention a patient is immobilized on a patient table that can be transported between these two medical apparatus. Furthermore, a relation is known between the reference co-ordinate systems of these two medical apparatus. After the selection of a
15 first relevant plane within the first data set and after assignment of the first co-ordinates to this first plane, the adjusting co-ordinates are applied to the X-ray apparatus via the data transmission cable. Subsequently, the patient is transported to the X-ray apparatus on the same patient table. The adjusting co-ordinates determine the position of the gantry of the X-ray apparatus relative to the patient table, so that an X-ray image can be formed. The X-ray
20 image of the patient formed in conformity with this method anatomically corresponds to the image of the first plane. This method of co-operation between an MR apparatus and an X-ray apparatus offers the advantage that the exposure projection of the patient by the X-ray apparatus is known a priori. On-line optimization of the exposure projection can thus be dispensed with, so that the overall radiation dose whereto the patient and the staff of the
25 operating room are exposed during such an intervention is reduced.

These and other aspects of the invention will be described in detail hereinafter with reference to some Figures; therein:

30 Fig. 1 illustrates diagrammatically the system for carrying out the method in accordance with the invention, and

Fig. 2 shows diagrammatically an example of a system as shown in Fig. 1 in which the apparatus are interconnected by a transmission cable.

Fig. 1 shows diagrammatically an embodiment of a system 100 that is formed by two imaging medical apparatus 10, 20 for carrying out the method for generating anatomically corresponding images in accordance with the invention. The first medical apparatus 1 includes means 11 for the acquisition of the first data set. For example, when the first imaging medical apparatus is an MR apparatus, the device for producing and detecting an RF signal forms part of the means for the acquisition of the first data set. In the case of an X-ray apparatus, the X-ray tube and the X-ray detector form part of the means for the acquisition of the first data set.

For the local assignment of the signal acquired from the studied volume within the patient to the setting of the first apparatus 10, the latter is provided with assignment means 12 which assign the first co-ordinates relative to the first imaging medical apparatus to a plane containing the first image. For cases where a first image that is relevant to the diagnosis is to be selected from the already acquired data set, the first imaging medical apparatus includes selection means 13. An example of such selection means consists of a computer program that executes a data processing step. The assignment means 12 subsequently assign the first co-ordinates to the selected image relative to the first imaging medical apparatus. The first imaging medical apparatus 10 also includes means 14 for making the first co-ordinates available to the second apparatus 20. An example of such means consists of a standard TCP/IP communication protocol. The patient is subsequently examined by means of the second imaging medical apparatus 20 which includes means 21 for the acquisition of an image. In order to adjust the second imaging medical apparatus 20 in conformity with the adjustment of the first imaging medical apparatus relative to the patient, the apparatus 20 includes means 24 for writing in the first co-ordinates made available by the first apparatus 10. This write step can be performed by way of a communication protocol that is known per se, for example by means of a TCP/IP protocol. When the second apparatus is of a type other than the first apparatus, it is necessary to perform a co-ordinate transformation from the first apparatus to the second apparatus. This step can be performed by means of translation means 26. An example of such translation means consists of a conversion table that is stored in the second apparatus. For the acquisition of an image that anatomically corresponds to the first image by means of the second apparatus, the latter must be adjusted in conformity with the first co-ordinates. This step is executed by means of adjusting means 25. Subsequently, the image anatomically corresponding to the first image is acquired by means of the means 21 of the second apparatus 20. If desired, the execution of the operational

steps concerning the making available of the first co-ordinates, the writing in of the first co-ordinates and the translation of the first co-ordinates to the co-ordinates that are suitable for the second apparatus can be delegated to a computer that is included in the system. An example in which said functionalities are delegated to the computer is diagrammatically represented by a functional block 30 in Fig. 1.

Fig. 2 illustrates diagrammatically the co-operation between two imaging medical apparatus 1, 2 for the execution of the method in accordance with the invention, said apparatus being interconnected by means of a data transmission cable 3. The first apparatus 1 is an MR apparatus and the second apparatus 2 is an X-ray apparatus. An example of such co-operation of the two imaging medical apparatus can be found in a suite for cranial interventions in which a region to be treated is defined by means of the MR apparatus and subsequently examined by means of the X-ray apparatus. A patient to be examined is immobilized on a patient table 4 that can be transported between the table support systems 6 and 8 of said apparatus. For a suitable operation of this assembly of medical apparatus it is desirable that the relationship of the respective co-ordinate systems is known and stored, for example, in one of the apparatus. The assembly operates as follows: first an image is formed by means of the MR apparatus 1. Subsequently, a patient is transported, on the same patient table 4, to the X-ray apparatus 2 whereby an anatomically matching image is to be formed. Because of the fact that the position of the patient relative to the patient table is not changed between the exposures by means of the medical apparatus 1 and 2, it is easy to adjust the means 21 for the acquisition of an image anatomically corresponding to the first image by the second apparatus 2. The necessary adjusting parameters are made available to the second apparatus via the data transmission cable 3.

CLAIMS:

1. A method of generating anatomically matching images by means of a system (100) which includes at least two imaging medical apparatus (10, 20), characterized in that the method includes the following steps:
 - acquisition of a data set containing a first image by means of a first apparatus
 - 5 (10);
 - selection of a plane containing the first image from the data set;
 - assignment of first co-ordinates relative to the first apparatus to the plane containing the first image;
 - making the first co-ordinates available to the second apparatus;
 - 10 - adjustment of the second apparatus (20) in conformity with the first co-ordinates;
 - formation of the second image while utilizing said adjustment.
2. A method as claimed in claim 1, wherein the first co-ordinates are made
- 15 available by means of a computer (30) included in the system.
3. A method as claimed in claim 2, wherein for each connected imaging medical apparatus (10, 20) a reference co-ordinate system is stored in a table present in the computer (30).
- 20 4. A method as claimed in claim 2 or 3, wherein the second reference co-ordinate system is calculated from the first reference co-ordinate system by the computer (30).
5. A method as claimed in claim 1, wherein a data set containing the first image
- 25 is stored in the computer (30) after acquisition by means of the first imaging medical apparatus.

6. A method as claimed in claim 1, wherein the first co-ordinates are made available via a cable (3) which directly interconnects two imaging medical apparatus (10, 20).

- 5 7. A system (100) for carrying out the method claimed in claim 1, including:
- a first imaging medical apparatus (10) for the acquisition of a first image;
 - a second imaging medical apparatus (20) for the acquisition of a second image that anatomically corresponds to the first image, characterized in that the system also includes:
- 10 - means (12) for assigning first co-ordinates relative to the first imaging medical apparatus (10) to a plane containing the first image;
- means (14) for making the first co-ordinates available to the second apparatus,
 - the second imaging medical apparatus being provided with adjusting means
- 15 (25) for adjusting this apparatus in conformity with the first co-ordinates.

8. A system as claimed in claim 7, also including a computer (30) which is arranged to make the first co-ordinates available to the second imaging medical apparatus.

20 9. A system as claimed in claim 8, wherein the computer (30) is provided with a table wherein a reference co-ordinate system is stored for each connected imaging medical apparatus.

10. A system as claimed in claim 7, wherein the first imaging medical apparatus
25 (1) is an MRI apparatus and the second imaging medical apparatus (2) is an X-ray apparatus, said apparatus being interconnected by means of a data transmission cable (3).

1/2




FIG. 1

2/2




FIG. 2

INTERNATIONAL SEARCH REPORT

Int. Application No

PCT/EP 01/07254

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A61B6/00 A61B5/055

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 945 103 A (SIEMENS AG) 29 September 1999 (1999-09-29) column 2, line 48 -column 3, line 5	1-9
A	column 6, line 47 -column 7, line 50	10
X	US 6 080 164 A (OSHIO KOICHI ET AL) 27 June 2000 (2000-06-27) column 2, line 54 -column 3, line 15	1-5,7-9
A	column 9, line 47 - line 62 column 15, line 10 - line 39; claim 3 --- -/--	6,10

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

6 December 2001

Date of mailing of the international search report

12/12/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3016

Authorized officer

Knüpling, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/07254

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PERIA O ET AL: "USING A 3D POSITION SENSOR FOR REGISTRATION OF SPECT AND US IMAGES OF THE KIDNEY" LECTURE NOTES IN COMPUTER SCIENCE, SPRINGER VERLAG, NEW YORK, NY, US, vol. 905, April 1995 (1995-04), pages 23-29, XP001035277 ISSN: 0302-9743	1,2,5-8
A	section 2 "Materials and Methods"	3,4,9,10
X	----- PATENT ABSTRACTS OF JAPAN vol. 1997, no. 05, 30 May 1997 (1997-05-30) & JP 09 024048 A (TOSHIBA CORP), 28 January 1997 (1997-01-28)	1,7
A	abstract	10
A	----- DE 39 31 531 A (SIEMENS AG) 5 April 1990 (1990-04-05) column 2, line 49 -column 3, line 24 -----	1,6,7,10

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int'l Application No

PCT/EP 01/07254

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0945103	A	29-09-1999	DE 19905532 A1	30-09-1999
			EP 0945103 A1	29-09-1999
			JP 11313814 A	16-11-1999
			US 6157697 A	05-12-2000
US 6080164	A	27-06-2000	US 2001020127 A1	06-09-2001
			AU 6907696 A	12-03-1997
			CA 2227275 A1	27-02-1997
			EP 0955932 A1	17-11-1999
			JP 11505356 T	18-05-1999
			WO 9706744 A1	27-02-1997
			ZA 9607029 A	15-05-1997
JP 09024048	A	28-01-1997	NONE	
DE 3931531	A	05-04-1990	DE 3931531 A1	05-04-1990